

# COUTURE

## PATTERNS

### CROP TOP ASH

Difficulty



Advanced



## **IMPORTANT!**

Permission to use patterns "Couture patterns":

- for personal use only. It is forbidden to send patterns "couture patterns" and patterns instructions to third persons, also post patterns and instructions in the public domain using the Internet and other digital networks. In accordance with the Law of the Republic of Belarus On Copyright and Related Rights of July 17, 2011 №262-3 ст.55 non-compliance of these rules is a violation of the current legislation in the field of copyright and the responsibility of the violator. Illegal use or distribution will be prosecuted in accordance with the legislation of the Republic of Belarus: Code of the Republic of Belarus On Administrative Violations of January 06, 2021 №91-3 and the Criminal Code of the Republic of Belarus dated July 09, 1999№275-3.
- for commercial purposes only when tailoring underwear to order, creating collections, provided that the patterns are used only in production without subsequent distribution to private individuals.

## MODEL DESCRIPTION

Comfort, elegance and freedom of movement in one crop top.

This universal not underwired crop top with lengthened body is an essential part of your lingerie wardrobe.

Soft silhouette, adjustable straps, side plastic bones provide maximum support and exceptional comfortable fit.

Center front detail forms a beautiful neckline in a natural way.



## REQUIRED TOOLS AND SUPPLIES

1. Sewing machine
2. Steam iron
3. Tailor's around last for wet heat treatment of a bra
4. Ironing board

You will also need tailor's needles, glue marker, ultra-fine pins, tailor's chalk, rotary cutter (normal scissors can be used, but we suggest using a rotary cutter for the most accurate cut), mat for cutting.

# MATERIALS FOR SEWING

## (CONSUMPTION OF MATERIALS FOR ALL SIZES)



1. Stretch atlas (tensile coefficient 0,85 weft) - 40 cm with a width of 1,2 m

2. Strap elastic width 1 cm или 2 cm - 1,4 m (length of basic strap 40 cm)

3. Band elastic width 1 cm - 1,5 m

4. Band elastic width 0,6 cm - 50 cm

5. 2 rings, 4 sliders, 1 G hook (or fastener «ring-hook») with a width corresponding to the width of the strap elastic.

6. Channeling width 1 cm - 50 cm

7. Hook & eye closure 2.8 cm wide- 1 pcs

8. Plastic bones length 15 cm - 2 pcs.

9. Reinforced sewing thread (thickness 100-120) - 1 spool.

and/ or on the looper textured thread (thickness 160-240)- 1 spool.

10. Needles super stretch 75/11 or stretch 75/11



\* use triple stitching - 2.5 stitch length

Carry out sewing of the central detail and the cup front detail with triple stretchy stitch.

Position of the needle in relation to the edge of the presser foot 5 mm

5mm — seam width

In tailoring, we mainly use a transparent presser

