

# COUTURE

## PATTERNS

TOP MOOD

Difficulty



Intermediate





## **IMPORTANT!**

Permission to use patterns "Couture patterns":

- for personal use only. It is forbidden to send patterns "couture patterns" and patterns instructions to third persons, also post patterns and instructions in the public domain using the Internet and other digital networks. In accordance with the Law of the Republic of Belarus On Copyright and Related Rights of July 17, 2011 №262-3 ст.55 non-compliance of these rules is a violation of the current legislation in the field of copyright and the responsibility of the violator. Illegal use or distribution will be prosecuted in accordance with the legislation of the Republic of Belarus: Code of the Republic of Belarus On Administrative Violations of January 06, 2021 №91-3 and the Criminal Code of the Republic of Belarus dated July 09, 1999№275-3.
- for commercial purposes only when tailoring underwear to order, creating collections, provided that the patterns are used only in production without subsequent distribution to private individuals.

# MODEL DESCRIPTION

Top with triangle cups, combining casual comfort with seductive style. Made of elastic lace fabric and elastic mesh. Without underwiring or padding.

A wide belt under the breasts is made of thick elastic bands, has supporting function besides the decorative one.

The plastic bones reinforces the side detail and gives additional support to the breast.

Adjustable straps.



## REQUIRED TOOLS AND SUPPLIES

1. Sewing machine
2. Steam iron
3. Tailor's around last for wet heat treatment of a bra
4. Ironing board

Also need tailor's needles, glue marker, ultra-fine pins, tailor's chalk, rotary cutter (you can use regular scissors, but suggest using a rotary cutter to get the most precise cut), cutting mat.

# REQUIRED MATERIALS

## (CONSUMPTION FOR ALL SIZES)



1. Mesh stretch (tensile coefficient 0,80 grain line, 0,70 weft) - 20 cm with a width of 1,2 m
2. Stretch lace fabric (tensile coefficient 0,70 grain line, 0,80 weft) - 40 cm with a width of 1,2 m

**\*we do not recommend using non-stretch lace fabric**

3. Strap elastic width 1 cm - 1 m (length of each strap 40 cm)
4. Band elastic width 1 cm or 0,8 cm - 1,5 m
5. Band ribbon width 3 cm- 40 cm
6. Elastic band 0,6 cm - 60 cm

7. 2 rings, 2 sliders— width 1 cm (width corresponding to the width of the strap elastic)

8. Channeling width 1 cm - 30 cm

9. Hook & eye width 2,8 cm –5,5 cm (the width is specified in the pattern) - 1 pcs.

10. Plastic bones, the length is specified in the pattern - 2 pcs.

11. Reinforced sewing thread (thickness 100-120) - 1 spool and/ or on the looper textured thread (thickness 160-240)- 1 spool.

12. Needles Super stretch or Stretch 75/11



**SEW THE BAND RIBBON ON THE LOWER EDGE OF THE CUP DETAIL OF THE TOP IN TWO STAGES.**

**2 STAGE**

\*Pay attention to the placement of the elastic edges relative to the presser.

\*use zigzag stitch  
Settings 2.5 x 2.5

Indent from the edge of the elastic—10mm



Turn the band ribbon to the inner side of the cup detail of the top.

When stitching the elastic band in 2nd stage, we only stretch it a little.

Slightly straighten the satin detail with hands so that unnecessary tucks don't form during stitching.